

Elmasonic S 15 (H)

Ultrasonic cleaning unit

Elma Order Nos.

Elmasonic S 15 (230 V)	100 4626
Elmasonic S 15 (115 V)	100 7138
Elmasonic S 15 H (230 V)	100 2060
Elmasonic S 15 H (115 V)	100 7139
Basket stainless steel	100 4209
Cover (plastic)	100 3280
Further accessories on request	



Pictured S 15 H

The new Elmasonic S units are available in 16 different sizes ranging from 0,5 litres to 90 litres. State-of-the art microprocessor controlled ultrasonic cleaning and sweep technology. The user-friendly LED-display ensures an excellent operation.

Further advantages:

- high-performance 37 kHz sandwich transducer systems
- cleaning tank made of cavitation-resistant stainless steel
- user-friendly and clear operating panel, splash water proof
- LED-Display showing set and remaining time of cleaning period
- Turning knob for setting continued and short-period operation from 1 to 30 min
- temperature-controlled ultrasonic operation (applies only for units with heating)
- sweep function for an optimised sound field distribution in the cleaning liquid by frequency modulation
- degas function for the efficient degassing of the cleaning liquid and for laboratory purposes
- auto degas function for automatic degassing cycles, i.e. with fresh cleaning liquids
- dry-run protected heating (applies only for units with heating)
- LED-Display for pre-set and actual temperature (applies only for units with heating)
- plug-in mains supply (S 10 – S 300H)

Technical data

Mains voltage (Vac)	100-120 V/220-240 V	Max. filling volume tank (lit. / gal.)	1,75 / 0.46
Ultrasonic frequency (kHz)	37	Weight (kg)	2,1
Power consumption total S 15 (W)	35	Material tank	stainless steel
Power consumption total S 15 H (W)	95	Material casing	stainless steel
Ultrasonic power effective (W)	35	Drain	/
Ultrasonic peak performance max.**(W)	280	Carrying handles (plastic)	/
Heating power (units w. heating) (W)	60	CE-compliant	√
Unit outer dimensions W / D / H (mm)	175 / 180 / 212	Protection class	IP 20
Tank internal dimensions W / D / H (mm)	151 / 137 / 100		
Basket internal dimensions W/D/H (mm)	112/ 103 / 50		

** S 10 – S 15 H: impulse wave form; S 30 – S 900 H: standard sine-wave modulation
The choice of the waveform has been matched to the relevant tank size. The signal form of the wave results in a factor 4 or 8 for the ultrasonic peak max., depending on the modulation of the wave.