

## Elmasonic S 80 (H)

### Ultrasonic cleaning unit

#### Elma Order Nos.

Elmasonic S 80 (230 V)	100 4652
Elmasonic S 80 (115 V)	100 7148
Elmasonic S 80 H (230 V)	100 2170
Elmasonic S 80 H (115 V)	100 7150
Basket stainless steel	100 4265
Cover (plastic)	100 3283
Further accessories on request	



Pictured S 80 H

The new Elmasonic S units are available in 16 different sizes ranging from 0,5 litres to 90 litres. State-of-the art microprocessor controlled ultrasonic cleaning and sweep technology. The user-friendly LED-display ensures an excellent operation.

Further advantages:

- high-performance 37 kHz sandwich transducer systems
- cleaning tank made of cavitation-resistant stainless steel
- user-friendly and clear operating panel, splash water proof
- LED-Display showing set and remaining time of cleaning period
- Turning knob for setting continued and short-period operation from 1 to 30 min
- temperature-controlled ultrasonic operation (applies only for units with heating)
- sweep function for an optimised sound field distribution in the cleaning liquid by frequency modulation
- degas function for the efficient degassing of the cleaning liquid and for laboratory purposes
- auto degas function for automatic degassing cycles, i.e. with fresh cleaning liquids
- dry-run protected heating (applies only for units with heating)
- LED-Display for pre-set and actual temperature (applies only for units with heating)
- plug-in mains supply (S 10 – S 300H)
- Plastic carrying handles, heat conducting
- Turning knob for tank drainage at side of unit for simple get effective draining of tank

#### Technical data

Mains voltage (Vac)	100-120 V/220-240 V	Max. filling volume tank (lit. / gal.)	9,4 / 2.48
Ultrasonic frequency (kHz)	37	Weight (kg)	6,4
Power consumption total S 80 (W)	150	Material tank	stainless steel
Power consumption total S 80 H (W)	750	Material casing	stainless steel
Ultrasonic power effective (W)	150	Drain	3/8"
Ultrasonic peak performance max. ** (W)	600	Carrying handles (plastic)	√
Heating power (units w. heating) (W)	600	CE-compliant	√
Unit outer dimensions W / D / H (mm)	568 / 179 / 264	Protection class	IP 20
Tank internal dimensions W / D / H (mm)	505 / 137 / 150		
Basket internal dimensions W / D / H (mm)	455 / 106 / 75		

\*\* S 10 – S 15 H: impulse wave form; S 30 – S 900 H: standard sine-wave modulation  
The choice of the waveform has been matched to the relevant tank size. The signal form of the wave results in a factor 4 or 8 for the ultrasonic peak max., depending on the modulation of the wave.