

elma clean 212 (EC 212)

CLEANING BOOSTER (TENSIDE COMPONENT)

LIQUID DEMULSIFYING RECYCLABLE CLEANING BOOSTER FOR THE ALKALINE IMMERSION CLEANING IN AN ULTRASONIC BATH

Description

Excellent as additive to basic cleaner components for the cleaning of:

- metal surfaces,
- numerous plastic surfaces,
- rubber and elastomer surfaces.

As additive to the alkaline basic component, *elma clean 212 (EC 212)* perfectly removes lapping and polishing pastes as well as:

- scaled and gummed oil and grease,
- wax (at the required temperature),
- residual lacquer and paint

Check any plastics for stress cracking resistance before use.

Application and dosage

To be used with an alkaline tenside-free basic component, such as *elma clean 112 (EC 112)*.

Dosage: 0.3 – 0.5 mass% in water, add alkaline basic component at 3 – 5 %.

Cleaning temperature: 40 - 90 °C. Cleaning time: 3 - 10 min in an ultrasonic bath.

Carefully rinse with water and dry.

Demulsifying. Suitable for recycling of the cleaning bath with membrane filtration.

Safety recommendations

elma clean 212 (EC 212) is classified as hazardous according to the regulation (EC) No 1272/2008 [GHS] (acutely toxic: harmful, serious eye damage, hazardous to the aquatic environment). Observe also with respect to this the hints indicated in the Safety Data Sheet and always handle chemicals with care.

Physical-chemical characterisation

Density: 1.024–1.036 g/ccm, pH (2% solution): 9 - 10.5. Ingredients according to Annex VII, A, EC-Regulation 648/2004 (detergents): >30% non-ionic surfactants.

Disposal

The surfactants in our product meet the criteria for biodegradation as laid down in Annex III of the Regulation (EC) No 648/2004 on detergents.

Cleaning baths containing this cleaning booster must not be fed into the public sewage system even after neutralization; they must be specially treated and disposed of according to the local sewage regulations.

European waste code: 20 01 29*, „detergents containing dangerous substances“.

Volumes, storage and transport

Available volumes: 1 litre PE-bottle; 2.5 litre, 10 litre and 25 kg HDPE-can; 200 kg barrel. Store in closed original container at a temperature between -5 °C and +30 °C, protected from heat and direct solar radiation; keep container dry and store at cool place.

Shelf life: 3 years from date of production (see stamp on label).

Classification for all means of transport: no hazardous material.

Elma Schmidbauer GmbH

Gottlieb-Daimler-Str. 17, D-78224 Singen

E-Mail: info@elma-ultrasonic.com

22.12.2016 / (GB) Version 2.3

Tel.: +49 7731 882-0

Fax: +49 7731 882-266

www.elma-ultrasonic.com

elma product info

